

# Boltaflex<sup>®</sup> Contract Upholstery

L'aria

## Product Specifications:

### General

Total Wt. - oz./sq. yd. (CFFA-700d)	8.0 ± .5
Total Wt. - oz./lin. yd. (CFFA-700d)	12
Width (min.) - in. (CFFA-700a)	54"
Face Content	Urethane

### Backing

Construction	Woven
Weight - oz./sq. yd.	4.5
Content	Poly/Cotton
Fiber Type	Spun

### Adhesion (CFFA-3)

Pounds/Inches (min.)	Warp 5.0
	Fill 5.0

### Tensile Strength (CFFA-17)

Pounds (min.)	Warp 100
	Fill 100

### Trap Tear Strength (CFFA-16c)

Pounds (min.)	Warp 15
	Fill 15

### Tack Strength (Stitch) (CFFA-14)

Pounds (min.)	Warp 65
	Fill 65

## Performance Testing: meets or exceeds

### Abrasion

Wyzenbeek, Wire Screen	10,000 cycles
Wyzenbeek, Cotton Duck	85,000 cycles

### Blocking (CFFA-4)

Pass

### W-Flex (CFFA-10)

25,000 cycles

### Crock (CFFA-7)

Pass

### UV (CFFA-2)

QUV	40 hours (indoors)
Xenon	100 hours

### Flame Retardancy

California Tech. Bulletin 117	Pass
UFAC Fabric, Class 1	Pass

## Miscellaneous:

### Application

Indoor

### Finish

Urethane



OMNOVA Solutions Inc. • Fairlawn, OH 44333 • www.omnova.com  
contact us at upholstery@omnova.com

BOLTAFLEX and PREFIX are registered trademarks of OMNOVA Solutions Inc.  
ALL OMNOVA PRODUCTS AND SERVICES ARE OFFERED AND SOLD SUBJECT TO THE OMNOVA  
STANDARD TERMS AND CONDITIONS OF SALE AGREEMENT SET FORTH AT WWW.OMNOVA.COM  
© 2010 OMNOVA Solutions Inc. QA#001-OT-001 Rev.10 • 02/02/10